

Campaign no.: 2009-0006

January 30, 2009

Subject: **DS 450 Xmx Tire Pressure Decal**

No. **2009-5**

YEAR	MODEL NAME	MODEL NUMBER	SERIAL NUMBER
2009	DS 450 Xmx	3H9A	See attached List

## PROBLEM

An incorrect tire pressure decal may have been installed on some units of the above mentioned model.

## SOLUTION

Update vehicles with a correct tire pressure decal. Correct tire pressure specification should be as per the following table.

TIRE PRESSURE		FRONT	REAR
Up to 100 kg (220 lb)	MAXIMUM	69 kPa (10 PSI)	62 kPa (9 PSI)
	MINIMUM	55 kPa (8 PSI)	48 kPa (7 PSI)

NOTE: The information is correct in the Operator's Guide.

## PARTS REQUIRED

### Tire Pressure Decal

DESCRIPTION	P/N	QTY
Tire pressure decal (English)	704 902 001	1
Tire pressure decal (French)	704 902 002	1

Order parts through the normal ordering channel.

## PROCEDURE

### Decal Location



vmo2008-011-023\_d  
TYPICAL - LH REAR FENDER  
1. Tire pressure decal

### Decal Installation

1. Clean the entire original decal surface and dry thoroughly.
2. Carefully install the new decal over the original decal.

## WARRANTY

### Involved Vehicles Claiming

Submit a warranty claim using the following information:

---

WARRANTY INFORMATION	
Campaign Number	2009-0006
Claim Type	Campaign Claim
Flat Rate	0.3 hour

## Claiming Procedure

For claiming procedure, refer to the *DEALER/DIS-TRIBUTOR WARRANTY GUIDE*.

---

# **SERIAL NUMBER LISTING OF MY 2009 INVOLVED VEHICLES**

***Model: 3H9A***

000001

From 000304 to 000354

From 000356 to 000386

From 000672 to 000777