



PIN ASSIGNMENT

P1(1)	—	P10(1)	—	P1(8)	—	P3
P1(2)	—	P10(2)	—	P1(9)	—	P8
P1(5)	—	P9	—	P1(10)	—	P6
P1(6)	—	P7	—	P1(11)	—	P4
P1(7)	—	P5	—	P1(12)	—	P2

LIST OF MATERIALS

TEM	DESCRIPTION	Qty
①	Cable: AMG26x10c Jacket OD=Ø6.0, Black L=0.75M	1
②	Cable: AMG20x2c Jacket OD=Ø4.5 Black L=1.5m	1
③	Cable: AMG20x1c Jacket OD=Ø2.8 Black L=0.95m	1
④	12P F Plug: PA66, black, Pins: chrome plated	1
⑤	Strain Relief: moulded PVC 45P, black	1
⑥	4mm round terminal: M, chrome plated, moulded pvc45p, black	4
⑦	4mm round terminal: F, chrome plated, moulded pvc45p, black	4
⑧	2P F plug: PA66, Pins: chrome plated, moulded PVC 45P, black	1
⑩	Tube: moulded PVC, black, Label: two sides, white	4

ELECTRONIC TEST:
 1.100% OPEN/CLOSE TEST
 2. CONTACT RESISTANCE: 1 OHM
 3. INSULATION RESISTANCE: 20M OHM
 4. DIELECTRONIC STRENGTH: 500VDC/10MS

TITLE
12P F to 4mm terminal&2P F Cable

AUTO TEST AID

SIZE	DWG NO	REV
A	90890-06894	00

PART #
 DRAWN
 DATE
 NAME

NOT TO SCALE

SHEET 1 OF 1